



- «Belarus» TTR-411 skidding tractor is designed for collecting of assortments, longwood and trunks at felling area, forming of bundles and their skidding at sanitary felling and also assortment stockpiling.
- It is based on the "Belarus L 1221" tractor.
- It is equipped with blade and "Taifun" EGV 60 AHK hydraulic winch.
- Has protective guards of cab, hood, head lights, tractor bottom.
- It is completed with wheels with heavy-duty rims, protection of tire valves, forestry tires with 420/70R24 front wheels and 18.4R38 rear wheels.
- Safety cab (ROPS, FOPS, OPS).
- Single delivery of blade, skidding device and protection guards.

ENGINE

Type	diesel
Model	D-260.2 turbo
Power, kW (hp)	96 (130)
Crankshaft rated speed, rpm	2100
Maximum torque, N•m	460
Fuel tanks capacity, l	160

TRANSMISSION

Clutch	dry, double-disk
Gearbox	mechanical, synchronized
Number of gears:	
forward	16
reverse	8
Travel speed, km/h:	
forward	2.1–20.0
reverse	4.0–15.4

DIMENSIONS AND WEIGHTS

Overall dimensions, mm:	
length	6160
width	2300
height	2970
Tread, mm	
front wheels (420/70R24)	1830
rear wheels (18.4R38)	1950
Road clearance, mm	470
Operating weight, kg	6450

SKIDDING EQUIPMENT

Winch	"TAJFUN" EGV 60 AHK
Winch drive	from rear PTO
Winch draft force, kN (kgf)	60 (6000)
Rope speed, m/sec	0.5–1.03
Rope cantilevering, m	110
Rope diameter, mm	12
Number of skid chain	5
Weight (without rope), kg	520

PUSHER

Width, mm	1800
Lifting height, mm	1200
Digging-in, mm	200